












	Model	isytech 34-10D	
	Code Production	917373	
Interface :			
			
			
	Overall Dimension (Width-Depth-Height) *open	mm	436x535(870*)x670
	Packaging Dimension (WxDxH)	mm	610x520x840
	Gross weight	Kg	34
	Net weight	Kg	31
	Volume	mc	0,27
	Rack size	mm	390x390
	Max door /hood opening	mm	320
	Max glasses/plate Height	mm	300/300
	General construction	stratified double	
	Door/hood Construction	double skin	
	Tank construction	welded	
	Tank volume	liter	8
	Tank heating element	W	600
	Tank surface strainers	Yes-composite	
	Wash pump type	double flow	
	Wash pump power	W	200
	Wash temperature	°C	60
	Boiler type	pressurized	
	Boiler volume	liter	2,6
	Back-flow system	valve	
	Boiler heating element	W	2.600
	Rinse booster pump	NO	
	Rinse booster pump power	W	-
	Rinse temperature	°C	65
	Rinse water consumption	Liter /rack	1,5
	Optimal external water pressure	bar	2 - 4
	Drain system	overflow	
	Drain filter	double filtering	
	Drain pump	optional	
	Rinse aid dispenser	peristaltic	YES
	Detergent dispenser	peristaltic	YES
	Wash cycle	sec	90 - 120 - 150
	Special cycle	programs	2
	Self cleaning cycle	YES	
	Electric Power	W	3.500
	Electric Connection	V - ph - Hz	230V 1N 50Hz
	Fuse	A	16
	Water softner	NO	
	Plates racks	n°-	NO
	Flat Rack	n°2	780133
	Support for saucers	n°-	NO
	Cutterly Rack	n°1	780139
	Electric cable	n°1	YES
	Drain hose	n°1	YES
	Fill hose	n°1	YES

