











 Model	isytech 32-10D.1	
Code Production	918211	
Interface :		



	Overall Dimension (Width-Depth-Height) *open	mm	600 - 700(1135*) - 850
	Packaging Dimension (WxDxH)	mm	700x800x1000
	Gross weight	Kg	67
	Net weight	Kg	61
	Volume	mc	0,55
	Rack size	mm	500 x 600
	Max door /hood opening	mm	405
	Max glasses/plate Height	mm	380
	Rack's drives/frame construction		flat
	Flanks construction		double skin
	Door/hood Construction		double skin
	Tank construction		welded
	Tank volume	liter	23
	Tank heating element	W	2.100
	Tank surface strainers		stainless steel
	Wash pump type		double flow
	Wash pump power	W	700
	Soft start		YES
	Wash temperature	°C	60 (45-->65)
	Boiler type		pressurized
	Boiler volume	liter	7
	Back-flow system		valve
	Boiler heating element	W	7.000
	Rinse booster pump		NO
	Rinse booster pump power	W	-
	Rinse temperature	°C	80 (80-->88)
	Rinse water consumption	Liter /rack	2,4
	Optimal external water pressure	bar	2 - 4
	Drain system		overflow
	Drain filter		double filter
	Drain pump		optional
	Rinse aid dispenser		YES
	Detergent dispenser		YES
	Water softner		NO
	Wash cycle	sec	120 - 240 - 360 - 480 - 600
	Special cycle	programs	n°3
	Self cleaning cycle		YES
	Electric Power	W	9.800
	Electric Connection	V - ph - Hz	400V 3N 50Hz
	Fuse	A	16
	Flat Rack in stainless steel 50x60	N°1	706129
	Grid for trays	N°	optional
	Electric cable		YES
	Drain hose		YES
	Fill hose		YES

