



RK505

Upright Cooler

Product features

- New design
- Reversible solid door
- Stainless steel
- Ventilated cooling
- Lock
- Self-closing door
- Adjustable shelves
- Strong wheels



Adjustable shelves




Automatic defrost system

| Design and Material | |
|---------------------|----------------------------------|
| No. of Doors | 1 |
| Door No & Type | 1 hinged self-closing solid door |
| No. of Shelves pcs | 3 |
| Shelves No & Type | 3 wire shelves white |
| Shelf Color | White |
| Shelf Dimensions | 530 x 540 |
| Castors | 4 wheels, 2 with brake |
| Exterior Finish | SS304 |
| Interior Finish | SS304 |
| Interior Light | No |
| Lock | Yes |

| Measures and Content | |
|-----------------------|-----------|
| Temperature Range °C | -2 to +8 |
| Climate Class | 4 |
| Gross / Net Weight kg | 132 / 127 |
| Gross / Net Volume l | 466 / 429 |

| Cooling and Functions | |
|-----------------------|------------|
| Type of Controller | Electronic |
| Type of Cooling | Ventilated |
| Type of Defrost | Automatic |
| Refrigerant | R600a |
| Refrigerant Charge g | 90 |
| Thermometer | Yes |
| GWP | 3 |

| Power and Consumption | |
|------------------------------------|---|
| Energy Class | C |
| Energy Arrow |  |
| Energy Consumption k | 1,12 |
| Annual Energy Consumption kWh/year | 409 |
| EEl % | 3 |
| EEl Vol l | 313 |
| Input Power W | 255 |
| Voltage / Frequency V/Hz | 220-240/50 |
| Noise Level db(A) | 45 |

| Dimensions | |
|-------------------------------|------------------|
| Internal Dimension (WxDxH) mm | 560 x 553 x 1386 |
| External Dimension (WxDxH) mm | 680 x 700 x 2010 |
| Packed Dimension (WxDxH) mm | 750 x 800 x 2150 |
| 40ft Container Load pcs | 48 |