



MD1402X

Stainless Steel Multideck

Product features

- Premium design
- Stainless steel exterior and interior
- Adjustable shelves with tilting function
- Temperature Class 3M1
- Shelf stopper for tilting is accessory
- LED interior light with switch
- Digital controller and temperature display
- Night blind / Curtain with soft release



Soft release night blind / curtain



Adjustable shelves with tilting function

Open front multideck with stainless steel interior and exterior

The TEFCOLD MD-X range of open front multidecks finished in stainless is a great choice for shops, cafes, sandwich shops, butchers and convenience stores. Available in different widths between 685mm and 1885mm there is a size to suit most situations.

The unit is only 680mm deep and is ideal where there is limited floor space but you need to maximise refrigerated display area. With a base shelf and 4 adjustable shelves there is plenty of product storage space. Mirror finish stainless steel interior helps give a sense of space within the cabinet while bright white vertical LED lighting gives excellent illumination of the product (the MD1902X also has a horizontal LED light across the top).

The temperature range can be adjusted to suit your requirement including fresh meat, dairy or soft drinks or beer. Shelves can be angled between 2 and 20 degrees to give extra merchandising options (front shelf stops are required if shelves are angled). The unit comes fitted with rollers to enable the unit to be moved for cleaning, there is also an option for castors. The unit is also available in black.

Design and Material

No. of Shelves	pcs	4
Shelves No & Type	4 SS304 shelves, tilting	
Shelf Color	Stainless steel	
Feet / Legs	2 adjustable feet	
Castors	4 rollers	
Exterior Finish	Stainless steel	
Interior Finish	Stainless Steel	
Interior Light	LED	

Measures and Content

Temperature Range	°C	-1 to +5
Climate Class	3	
Gross / Net Weight	kg	210 / 188
Gross / Net Volume	l	913 / 665

Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic	
Refrigerant	R290	
Refrigerant Charge	g	135

Power and Consumption

Energy Class	E	
Energy Consumption	kWh/24h	19,1
Annual Energy Consumption	kWh/year	6971,5
EEL	%	63,6
Power	1	
Max Ambient	25°C at 60% RH	
Input Power	W	920
Voltage / Frequency	V/Hz	220-240/50
Noise Level	db(A)	55

Dimensions

Internal Dimension (WxDxH)	m	1250 x 560 x 1355
External Dimension (WxDxH)	m	1335 x 680 x 1985

Power and Consumption

Packed Dimension (WxDxH)	m	1420 x 750 x 2140
	m	
40ft Container Load	pcs	25