

## EXTRA1450CD

Supermarket Multideck Cooler

## **Product features**

- Can be multiplexed Create uninterrupted continuous line
- Temperature Class 3M1
- Heavy duty shelving with strengthening bar
- · Adjustable extra deep shelves to maximise capacity
- Tilting function for better product display
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Glass end walls as standard
- Multiplexing kit as accessory



Glass end walls as standard



Adjustable shelves with tilting function

## Full Glass Door Multideck Cooler with Multiplexing Option

EXTRA Multideck is a full glass door quality cooler with double glazed hinged glass doors for added energy efficiency savings on running costs.

For greater stock capacity it has 450mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Shelves can be flat or tilted to 10 or 20 degrees with ticket strips and shelf risers as standard.

It is suitable for display of packed fresh meat, dairy or drinks and is ideal for supermarkets, convenience stores, delis and sandwich shops where plug-in refrigeration is required.

Installation is simple and quick. No special requirements as refrigerant charge is below 150g.

The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Design and Material				
Door No & Type	2	2 hinged glass doors		
Door Reversible		No		
Shelves No & Type	4 black sheet, tilting + base			
Shelf Color		Black		
Max Load of Shelves	kg/m²	100		
Feet / Legs		4 adjustable feet		
		Option		
Exterior Finish		Black / Glass		
Interior Finish		Black		
Interior Light		2 x Vertically LED		

Measures and Content				
Total Display Area	m²	2,12		
Temperature Range	°C	+2 to +6		
Climate Class		3		
Gross / Net Weight	kg	400 / 370		
Gross / Net Volume	I	1050 / 900		

Cooling and Functions		
Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	

Power and Consumption				
Energy Class		D		
EnergyConsumption	kWh/24h	12,44		
Annual Energy Consumption	kWh/year	4541		
Input Power	W	1200		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	db(A)	53		

Dimensions		
Internal Dimension (WxDxH)	mm	1450 x 610 x 1399

Design and Material
Lock No

Measures and Content
Thermometer Yes

Power and Consumption

External Dimension mm 1550 x 920 x 2035 (WxDxH)

Packed Dimension mm 1650 x 975 x 2230 (WxDxH)

40ft Container Load pcs 14