

## EXTRA1875CD

### Supermarket Multideck Cooler



#### Product features

- Can be multiplexed - Create uninterrupted continuous line
- Temperature Class 3M1
- Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Tilting function for better product display
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Glass end walls as standard
- Multiplexing kit as accessory



Glass end walls as standard



Adjustable shelves with tilting function

### Full Glass Door Multideck Cooler with Multiplexing Option

EXTRA Multideck is a full glass door quality cooler with double glazed hinged glass doors for added energy efficiency savings on running costs.

For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Shelves can be flat or tilted to 10 or 20 degrees with ticket strips and shelf risers as standard.

It is suitable for display of packed fresh meat, dairy or drinks and is ideal for supermarkets, convenience stores, delis and sandwich shops where plug-in refrigeration is required.

Installation is simple and quick. No special requirements as refrigerant charge is below 150g.

The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Design and Material		Measures and Content		Power and Consumption	
Door No & Type	3 hinged glass doors	Total Display Area	m <sup>2</sup> 2,72	Energy Class	C
Door Reversible	No	Temperature Range	°C +2 to +6	EnergyConsumption	kWh/24h 14,03
Shelves No & Type	4 black sheet, tilting + base	Climate Class	3	Annual Energy Consumption	kWh/year 5119
Shelf Color	Black	Gross / Net Weight	kg 475 / 425	Input Power	W 1300
Max Load of Shelves	kg/m <sup>2</sup> 100	Gross / Net Volume	l 1350 / 1160	Voltage / Frequency	V/Hz 220-240/50
Feet / Legs	6 adjustable feet	Cooling and Functions		Noise Level	db(A) 53
Castors	Option	Type of Controller	Electronic	Dimensions	
Exterior Finish	Black / Glass	Type of Cooling	Ventilated	Internal Dimension (WxDxH)	mm 1875 x 610 x 1399
Interior Finish	Black	Type of Defrost	Automatic, hot gas		
Interior Light	2 x Vertically LED	Refrigerant	R290		

**Design and Material**

Lock	No
------	----

**Measures and Content**

Refrigerant Charge	g	2x144
Thermometer		Yes

**Power and Consumption**

External Dimension (WxDxH)	mm	1975 x 920 x 2035
Packed Dimension (WxDxH)	mm	2075 x 975 x 2230
40ft Container Load	pcs	12